

In the Claims

1
2 1. (Currently Amended) A fuel cell system, configured to control temperature
3 by regulating serial vs. parallel configuration of fuel cells within the system, the
4 system comprising:

5 first and second fuel cells capable of providing an electrical output; and

6 a controller configured for regulating temperature of the fuel cell system by
7 controlling serial vs. parallel configuration of the first and second fuel cells,
8 wherein the controller is configured to identify whether more or less heat is
9 required by the fuel cell system, and wherein the controller is in communication
10 with:

11 a switch circuit comprising one or more switches for arranging the
12 electrical output of the first fuel cell and the electrical output of the second fuel
13 cell in parallel or series; and

14 a temperature measurement circuit capable of measuring the
15 temperature of the first fuel cell or the second fuel cell and providing a signal to
16 the controller;

17 wherein the controller utilizes the switch circuit to switch to a more serial
18 configuration if more heat is required and switches to a more parallel
19 configuration if less heat is required.

20
21 2. (Canceled)

22
23 3. (Original) The system of claim 1, wherein the first fuel cell and the second
24 fuel cell comprises solid oxide fuel cells.

1
2 4. (Previously Presented) The system of claim 1, wherein the controller
3 increases heat production by increasing fuel consumption by switching to a more
4 serial configuration and decreases heat production by decreasing fuel consumption
5 by switching to a more parallel configuration.

6
7 5. (Previously Presented) The system of claim 4, wherein the controller is
8 configured to receive the signal from the temperature measurement circuit and to
9 arrange the electrical output of the first fuel cell and the electrical output of the
10 second fuel cell in response thereto.

11
12 6. (Original) The system of claim 4, wherein the controller causes the switch
13 circuit to arrange the electrical output of the first fuel cell and the electrical output
14 of the second fuel cell in parallel to increase electrical output efficiency of the first
15 fuel cell and the second fuel cell.

16
17 7. (Original) The system of claim 4, wherein the controller causes the switch
18 circuit to arrange the electrical output of the first fuel cell and the electrical output
19 of the second fuel cell in series to decrease electrical output efficiency of the first
20 fuel cell and the second fuel cell.

21
22 8.—23. (Cancelled)

1 24. (Currently Amended) A fuel cell system comprising:

2 means for supplying an excess amount of fuel to a multiple fuel cell
3 system;

4 means for switching at least some of the fuel cells from a parallel electrical
5 arrangement to a series electrical arrangement; and

6 means for producing heat from at least some of the excess amount of fuel,
7 wherein the means for producing heat switches to a more serial configuration if
8 more heat is required and switches to a more parallel configuration if less heat is
9 required by the fuel cell system.

10
11
12 25. (Currently Amended) A fuel cell system comprising:

13 means for supplying a substantially constant amount of fuel to a multiple
14 fuel cell system;

15 means for switching at least some of the fuel cells from a series electrical
16 arrangement to a parallel electrical arrangement, wherein the means for switching
17 switches to a more serial configuration if more heat is required and switches to a
18 more parallel configuration if less heat is required by the fuel cell system;

19 means for increasing EMF efficiency; and

20 means for reducing fuel efficiency.

21
22 26. (Cancelled)

23
24 27. (Cancelled)

1
2 28. (Currently Amended) A fuel cell system, configured to control temperature
3 of the fuel cell system by regulating a serial vs. a parallel configuration of cells
4 within the system, the fuel cell system comprising:

5 a controller configured to identify whether more or less heat is required by
6 the fuel cell system, and to increase or decrease heat ~~provided to~~generated by the
7 fuel cell system by regulating a serial vs. a parallel configuration of cells within
8 the system;

9 a temperature measurement circuit, in communication with the controller,
10 configured to measure temperature of at least one fuel cell and to provide a signal
11 to the controller; and

12 a switching circuit to arrange the first and second fuel cells in a parallel or a
13 series configuration in response to the controller;

14 wherein the controller utilizes the switching circuit to switch to a more
15 serial configuration if more heat is required and to switch to a more parallel
16 configuration if less heat is required.

17
18 29. (Previously Presented) The fuel cell system of Claim 28, wherein the
19 controller alternates between increased heat production associated with a more
20 serial configuration of the cells within the system and decreased heat production
21 associated with a more parallel configuration of the cells within the system to
22 provide fuel cell modulation and temperature control to the fuel cell system.
23
24
25

1 30. (Previously Presented) The fuel cell system of Claim 28, wherein the
2 controller directs an excess supply of fuel to the system prior to identification of
3 heat requirements of the fuel cells.
4

5 31. (Currently Amended) The fuel cell system of Claim 28, wherein the
6 controller iteratively measures fuel cell temperatures and iteratively reconfigures
7 the fuel cell system in a more parallel or more serial configuration in response to
8 changes in temperature changes of the fuel cell system.
9

10 32. (Previously Presented) The fuel cell system of Claim 28, wherein the
11 controller is configured to supply an excess amount of fuel to multiple fuel cells,
12 to receive a temperature measurement from the temperature measurement circuit,
13 to switch at least some of the fuel cells from a parallel electrical arrangement to a
14 series electrical arrangement using the switching circuit in response to the
15 measured temperature, and to thereby produce heat from at least some of the
16 excess amount of fuel.
17

18 33. (Previously Presented) The fuel cell system of Claim 28, wherein the
19 controller is configured to supply an excess amount of fuel to multiple fuel cells,
20 to switch at least some of the fuel cells from a parallel electrical arrangement to a
21 series electrical arrangement, and to produce heat from at least some of the excess
22 amount of fuel.
23
24
25

1 34. (Previously Presented) A fuel cell system, configured to alternate between
2 serial vs. parallel configurations of fuel cells within the system based on heat
3 required by the system, the fuel cell system comprising:

4 means for controlling the fuel cell system, wherein the means for
5 controlling is configured to identify whether more or less heat is required by the
6 fuel cell system;

7 means for measuring temperature within one or more fuel cells and for
8 communicating with the means for controlling the fuel cell; and

9 means for switching the fuel cells between a parallel configuration and a
10 serial configuration, in response to direction from the means for controlling the
11 fuel cell;

12 wherein the means for controlling the fuel cell utilizes the means for
13 switching to switch the fuel cell system to a more serial configuration if more heat
14 is required and to switch the fuel cell system to a more parallel configuration if
15 less heat is required.

16
17 35. (Previously Presented) The fuel cell system of Claim 34, wherein the means
18 for controlling is configured to switch fuel cells from a series electrical
19 arrangement to a parallel electrical arrangement to increase EMF efficiency and
20 reduce fuel efficiency.

21
22 36. (Previously Presented) The fuel cell system of Claim 34, wherein the fuel
23 cells within the system comprise solid oxide fuel cells.
24
25

1 37. (Previously Presented) The fuel cell system of Claim 34, wherein the means
2 for controlling iteratively receives fuel cell temperature measurements and
3 iteratively reconfigures the fuel cell system in a more parallel or more serial
4 configuration in response to temperature changes.

5
6 38. (Previously Presented) The fuel cell system of Claim 34, wherein the means
7 for controlling is configured to supply an excess amount of fuel to multiple fuel
8 cells, to receive a temperature measurement from the temperature measurement
9 circuit, to switch at least some of the fuel cells from a parallel electrical
10 arrangement to a series electrical arrangement using the switching circuit, and to
11 thereby obtain heat from at least some of the excess amount of fuel.

12
13 39. (Previously Presented) The fuel cell system of Claim 34, wherein the means
14 for controlling is configured to supply a substantially constant amount of fuel to
15 multiple cells within the fuel cell system, to switch at least some of the fuel cells
16 from a series electrical arrangement to a parallel electrical arrangement, and to
17 thereby increase EMF efficiency and reduce fuel efficiency.

1 40. (Previously Presented) A fuel cell system, configured to regulate
2 temperature by alternating between increased and decreased heat production, the
3 fuel cell system comprising:

4 a temperature measurement circuit configured to measure temperature of
5 fuel cells within the system;

6 a switching circuit to change an arrangement of the fuel cells in either
7 direction between a parallel configuration and a serial configuration; and

8 a controller configured to receive temperature measurement information
9 from the temperature measurement circuit, to determine whether more or less heat
10 is required by the fuel cell system, and to control the switching circuit and the
11 configuration of the fuel cells, wherein the controller utilizes the switching circuit
12 to switch to a more serial configuration if more heat is required and to switch to a
13 more parallel configuration if less heat is required.

14
15 41. (Previously Presented) The fuel cell system of Claim 40, wherein the
16 controller is configured to switch fuel cells from a series electrical arrangement to
17 a parallel electrical arrangement to increase EMF efficiency and reduce fuel
18 efficiency.

19
20 42. (Previously Presented) The fuel cell system of Claim 40, wherein the
21 controller is configured to switch fuel cells between a series electrical arrangement
22 that increases fuel consumption and heat production and a parallel electrical
23 arrangement that decreases fuel consumption and heat production.
24
25

1 43. (Currently Amended) The fuel cell system of Claim 40, wherein the
2 controller iterates in a cycle of measuring fuel cell temperatures and reconfiguring
3 the fuel cell system in a more parallel or more serial configuration in response to
4 changes in temperature changes of the fuel cell system.

5
6 44. (Previously Presented) The fuel cell system of Claim 40, wherein the
7 controller is configured to supply an excess amount of fuel to multiple fuel cells,
8 to switch at least some of the fuel cells from a parallel electrical arrangement to a
9 series electrical arrangement using the switching circuit, and to thereby produce
10 heat from at least some of the excess amount of fuel.

11
12 45. (Previously Presented) The fuel cell system of Claim 40, wherein the
13 controller is configured to supply a substantially constant amount of fuel to
14 multiple cells within the fuel cell system, to switch at least some of the fuel cells
15 from a series electrical arrangement to a parallel electrical arrangement, and to
16 thereby increase EMF efficiency and reduce fuel efficiency.